

## **VR6D-HS**



The VR6D-HS is the most advanced 127 cm x 254 cm flatbed on the market today. It combines the latest state-of-the-art Ricoh Gen 6 print head technology and high-speed magnetic drive unparalleled speed, resolution and quality.

### **THE POWER OF LED TECHNOLOGY:**

- Extends your range of supported substrates, including lower-cost and added-value specialty media
- Increases uptime and productivity with instant on/off and less maintenance
- Drives down operating costs with less energy consumption and fewer consumable parts
- Reduces waste with consistent color output and simple operation
- Satisfies customer requests for a greener print solution with low VOCs, lower power consumption, and less waste and consumables

### **PRECISE AND ACCURATE DOT PLACEMENT FROM PRINT TO PRINT:**

- New magnetic linear drive control
- High-volume ink jetting at an accurate level to support productivity
- Solid aluminum table with flatness of +/- 50 microns
- Four-zone, user-selectable vacuum system ensures efficient hold-down, no unintended media movement, and easy transitions between jobs

### **HIGH PRODUCTIVITY AND IMAGE QUALITY AT A COMPETITIVE PRICE:**

- CMYK + White + Varnish with singlepass, multi-layer printing
- 3 Level Greyscale with variable drop technology 5 picoliter drop sizes for better color gradients and smoothing capability
- Precise dot placement for sharper lines and text and less overspray
- Durst Workflow prepress & RIP software solution with Vanguard interactive G.U.I.

#### **SINGLE ROW PRINT SPEEDS**

Production	Up to 74 m/h
Quality	Up to 33 m/h
High Quality	Up to 24 m/h

#### **DUAL ROW PRINT SPEEDS**

Production	Up to 119 m/h
Quality	Up to 55 m/h
High Quality	Up to 36 m/h

# VIR6D-HS

## SPECIFICATIONS

Print Head	Ricoh Gen6	W x D x H	467 cm x 200 cm x 145 cm
Print Resolution	Up to 1800 apparent dpi As small as 5 pL	Crated W x D x H	546 cm x 226 cm x 188 cm
Qty. of Heads	Up to 10 (5x2 rows)	Weight	1,588 kg
Base Ink	CMYK	Weight Crated	1,844 kg
Optional Ink	w,v, lc, lm, spot	Operating Dimensions	343 cm x 635 cm
Curing	Liquid Cooled LED	Minimum Door Clearance	183 cm

## DIMENSIONS

## REQUIREMENTS

Power	2 x 200 V, 1 phase, 32 amps 1 x 100 V, 1 phase, 16 amps	Max Print Size	127 cm x 254 cm
Environment	Dust free / climate controlled	Max Thickness	Up to 10 cm thick
Temperature	19-31 C	Max Weight	227 kg
Humidity	40-70% non-condensing	Material Type	Rigid & flexible
Network	Connection optional	Best Media	UV acceptable

## MEDIA

## PERIPHERALS

Computer	Integrated PC
Control Software	Integrated
Rip Solution	Durst Workflow
Processor	Intel

POWERED BY



DURST **LSWA**  
SOFTWARE &  
SOLUTIONS

## Growing Your Business Together

Vanguard Europe  
Julius-Durst Strasse 2/C  
39042 Brixen  
Italy

+ 39 0472 810444  
info@vanguarddigital.com  
www.vanguarddigital.eu



**VANGUARD**  
DIGITAL PRINTING SYSTEMS  
A Durst Group Company